



### Taper Legend

POSTED SPEED	TAPER LENGTH* "L"			MINIMUM CHANNELIZING DEVICES NEEDED	MAXIMUM DISTANCE BETWEEN DEVICES ALLOWED	BUFFER ZONE LENGTH
	10' LANE	11' LANE	12' LANE			
25	104'	115'	125'	6	25'	155'
30	150'	165'	185'	7	30'	200'
35	204'	225'	245'	8	35'	250'
40	267'	293'	320'	9	40'	305'
45	450'	495'	540'	13	45'	360'
50	500'	550'	600'	13	50'	425'
55	550'	605'	660'	13	55'	495'

\*Merging Tapers = "L", Shifting Tapers = "L/2" & Shoulder Tapers = "L/3"  
Tangential Spacing not to exceed 2 times Posted Speed Limit, in feet, as per the MUTCD Sec 6F.58

SIGN SPACING = 10X POSTED SPEED LIMIT

NOTE: Signs will be double indicated when feasible.  
NOTE: Adjustments to sign spacing & channelization devices, for vertical and horizontal curves, side roads and driveways shall be made in field.

DESIGNED BY
TRAFFIC CONTROL CONTRACTOR <b>HIGHWAY SUPPLY LLC</b>
Phone 505-345-8295x116 FAX 505-345-0546 EMAIL r.lindsey@highwaysupply.net
Reviewed By:
<input type="checkbox"/> Approved <input type="checkbox"/> Approved As Amended <input type="checkbox"/> Correct and Resubmit